



**Quality and Reliability, Since 1932!**


# VALVE FITTINGS & ACCESSORIES

## SINGLE POPPET SAFETY VALVES

### Application -

Maximizes safety, and prevents fuel spillage and fire hazard.

**Part Number - 521, 522** Patent Number 3,378,021



**UNIVERSAL**  
**Advantage**

Only from Universal! The safest safety valve!  
The poppet and seat are completely independent of the top shear section, so even with the top off, the valve assures a 100% liquid tight seal.

### Features -

- ✓ A 100% seal
- ✓ Unobstructed flow
- ✓ The poppet and seat are completely independent of the top shear section, so even with the top off, the valve assures a 100% liquid tight seal
- ✓ The single-link design provides ease of operation and reduced maintenance
- ✓ A stainless steel reset nut eliminates stripping the fusible link during valve reset, reducing downtime by allowing manual reset even under pressure
- ✓ All Universal Safety Valves are protected by zinc plating, assuring maximum corrosion resistance, unlike competitive products that are only painted
- ✓ An air test port allows line testing without breaking the integrity of the line
- ✓ Raised bosses provide secure anchoring

### Construction -

- Zinc-plated cast iron body and top
- Stainless steel spring and shaft
- Bun-N seal

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

**UNIVERSAL VALVE COMPANY**

478 Schiller Street, Elizabeth, NJ 07206 • (800) 223-0741 • (908) 351-0606 • Fax: (908) 351-0369 • [universalvalve.com](http://universalvalve.com)

© 2003 Universal Valve Company, Inc.



**The Most Complete Line of UST/AST Products!**

# VALVE FITTINGS & ACCESSORIES


## SINGLE POPPET SAFETY VALVES (CONTINUED)

Model	Top Thread	Size	Weight (lbs.)	A	B	C
521RFS-15	Female	1-1/2"	5.2	2-3/4"	4-1/2"	6-3/8"
521RMS-15	Male	1-1/2"	5.3	2-3/4"	4-1/2"	6-13/16"
521RUS-15	Union	1-1/2"	6.3	2-3/4"	4-1/2"	7-5/16"
522RFS-15	Female	1-1/2"	5.2	2-3/4"	4-1/2"	6-3/8"
522RMS-15	Male	1-1/2"	5.3	2-3/4"	4-1/2"	6-13/16"
522RUS-15	Union	1-1/2"	6.3	2-3/4"	4-1/2"	7-5/16"

Should an original Universal Safety Valve be sheared, or it's top become damaged, Universal offers replacement tops.

### Replacement Tops -

Model	Description
521RF-15-C	Female Single Poppet Top
521RM-15-B	Male Single Poppet Top
521RM-15-D	Single Poppet With 2/3 Union



Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

### UNIVERSAL VALVE COMPANY

478 Schiller Street, Elizabeth, NJ 07206 • (800) 223-0741 • (908) 351-0606 • Fax: (908) 351-0369 • universalvalve.com

© 2003 Universal Valve Company, Inc.